Application Board 2.0 (BT)

Bosch Sensortec





Description

The Bosch Sensortec Application Board 2.0 is a versatile, demonstration and development environment for Bosch Sensortec sensor products. Based on a powerful ARM Cortex-M4 μ Controller the Application Board can be used to configure all sensor parameters by means of PC-based software (Desktop Development). Sensor data can be read-out, displayed and captured on the attached PC.

The Application Board 2.0 applies a flexible shuttle-board concept. All sensor shuttle boards have identical footprint and can be plugged into the Application Board's shuttle-board socket. The PC software autonomously detects the sensor that has been plugged-in and starts the corresponding software application.

Key features

- ▶ Interface to Bosch Sensortec sensor shuttle boards
- ▶ USB 2.0 full speed connection to PC
- ► Flexible power supply (USB bus powered and battery with charger logic)
- ▶ 4 push buttons
- ► Firmware can be upgraded via Development Desktop 2.0
- Multiple test points and connectors to access data directly from the board
- ▶ Bluetooth interface (Application Board 2.0 BT only)

Deliverables

- Application Board 2.0 or Application Board 2.0 BT hardware
- ▶ Documentation
- Note: Sensor shuttle boards must be ordered separately

Windows 7 / 8.x are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Note: Product photo may differ from real product's appearance.

Headquarters Bosch Sensortec GmbH

Gerhard-Kindler-Strasse 8 72770 Reutlingen · Germany Telephone +49 7121 3535 900 Fax +49 7121 3535 909 contact@bosch-sensortec.com www.bosch-sensortec.com

Doc.-Number: BST-DHW-FL005-01 / Version 2.0 122013