

# ST25TA SERIES

## NFC Forum Type 4



### NFC tags with ISO/IEC 14443 Type A RF interface, NDEF memory, 128-bit password protection and TruST25 digital signature

ST's ST25TA ICs provide the NFC Forum Type 4 Tag RF interface and built-in NDEF (NFC Data Exchange Format) message support. The embedded EEPROM memory density spans from 512 bits to 64 Kbits, covering a wide spectrum of applications including content-rich virtual business cards and smart signs. The ST25TA series delivers state-of-the-art RF performance and features a user-programmable digital CMOS (or Open Drain) output that eliminates the need for an external component to trigger the host wake-up.

#### KEY FEATURES & BENEFITS

- ISO/IEC 14443 Type A
- NFC Forum Type 4 Tag
- 13.56 MHz carrier frequency
- 512-bit, 2-Kbit, 16-Kbit and 64-Kbit density memory
- 56-bit unique identifier
- 128-bit password protection
- Optional 20-bit counter
- Optional RF status digital output
- 5-lead UDFPN packages
- Bumped wafer die form packages
- 25 or 50 pF tuning capacitance
- 200 years data retention
- 1 million write erase cycles
- TruST25 digital signature

#### KEY BENEFITS

- Wide memory density options
- High-reliability EEPROM
- Built-in NDEF format support
- Strong password protection scheme
- Read or Write operations counter
- Flexible user-programmable GPO

#### KEY APPLICATIONS

Smart posters, NFC business cards, consumer electronics, wireless handover, gaming, industrial, traceability, wearable electronics, computer peripherals

## Device summary

Part number	RF interface	Memory size	Data protection (128 bit password)	20 bit Counter	Package	RF status output	Trust25 digital signature
ST25TA512B	ISO 14443A Type A	512 bit	Yes	Yes	SBN12 *, SBN075	No	Yes
ST25TA02KB	ISO 14443A Type A	2 Kbit	Yes	Yes	SBN12 *, SBN075	No	Yes
ST25TA02KB-P	ISO 14443A Type A	2 Kbit	Yes	Yes	UFDFPN5, SBN12*, SBN075	Yes (CMOS positive GPO)	Yes
ST25TA02KB-D	ISO 14443A Type A	2 Kbit	Yes	Yes	UFDFPN5, SBN12 *, SBN075	Yes (Open Drain GPO)	Yes
ST25TA16K	ISO 14443A Type A	16 Kbit	Yes	No	SBN12 *	No	No
ST25TA64K	ISO 14443A Type A	64 Kbit	Yes	No	SBN12 *	No	No

SBN075 : Sawn and Bumped wafer (die form), 75 µm thickness

## Reference design kits

The CLOUD-ST25TA02KB is a ready-to-use demo board intended to evaluate the ST25TA02KB-P (order code: CLOUD-ST25TA)



## Eco-system



Support eco-system



e2e community



PC SW tools



Documentation



Evaluation board



iOS NFC Tap app



ST25 NFC Tap app



Antenna Design Suite

## Technical support

The NFC/RFID tags family offers a simple and cost-effective implementation. ST can provide supporting material for integrating the antenna into your application: application notes, reference designs, antenna computation tools, e-presentations and e-learning.

Visit [www.st.com/nfc-rfid](http://www.st.com/nfc-rfid)



© STMicroelectronics - June 2020 - Printed in United Kingdom - All rights reserved  
 ST and the ST logo are registered and/or unregistered trademarks of STMicroelectronics International NV or its affiliates in the EU and/or elsewhere. In particular, ST and the ST logo are Registered in the US Patent and Trademark Office.  
 For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks).  
 All other product or service names are the property of their respective owners.

