

specificazioni	
Numero di parte	S2S3B00F
fabbricante	Sharp Microelectronics
Descrizione	OPTOISOLATOR 3.75KV TRIAC 4SMD
Categoria	isolatori > Optoisolatori - Triac, uscita SCR
Stato parte	5571 pcs Stock
Serie	-
temperatura di esercizio	-30°C ~ 100°C
Approvazioni	CSA, UR
Tipo montaggio	Surface Mount
Tipo di uscita	Triac
Numero di canali	1
Contenitore / involucro	4-SMD
Contenitore dispositivo fornitore	4-SMD
Tensione - Stato off	600V
Corrente - Mantenimento (Ih)	3.5mA
Tensione - Isolamento	3750Vrms
Corrente - Stato On (It (RMS)) (max)	50mA
Tensione - Forward (Vf) (Typ)	1.2V
Corrente - DC Forward (If) (Max)	50mA
Diametro albero (mm)	No
DV / dt statico (Min)	100V/μs
Corrente - Trigger LED (Ift) (Max)	10mA
Attiva ora	100μs (Max)
imballaggio	Tape & Reel (TR)

 S2S3AD0F Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S3L00F SHARP S2S3L00F SHARP	 S2S3AD0F Socle Technology Corporation OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S3AY0F SHARP S2S3AY0F SHARP
 S2S3AY Sharp Microelectronics S2S3AY SHARP	 S2S3LA0F Socle Technology Corporation OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S3BY Sharp Microelectronics S2S3BY SHARP	 S2S3B Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD

Di Più

Contact us: **Info@YIC-Electronics.com**

AGGIUNGI: Unità A5-B5 n. 509, 5 / F Sing Win Factory Building, 15-17 Shing Yip St, Kwun Tong, Kowloon, Hong Kong.

Copyright © 2018 YIC-Electronics.com - YIC International Co., Limited