



specificazioni	
Modello di prodotti	SX1441I077TRLF
fabbricante	Semtech
Descrizione	IC RF TXRX+MCU BLUETOOTH 72LFBGA
Categoria	RF / IF e RFID > Ricetrasmittitore RF ICS
Stato parte	4839 pcs Stock
Tensione di alimentazione -	2 V ~ 3.6 V
Digitare	TxRx + MCU
Serie	-
Interfacce seriali	SPI, UART
sensibilità	-
Famiglia RF / Standard	Bluetooth
Protocollo	Bluetooth v1.2
Alimentazione - uscita	-
imballaggio	Tape & Reel (TR)
Contenitore / involucro	72-LFBGA
temperatura di esercizio	-40°C ~ 85°C
Modulazione	-
Dimensione della memoria	4kB ROM, 40kB RAM
GPIO	8
Frequenza	2.4GHz
Tasso di dati (massimo)	921kbps
Corrente - trasmissione	-
Corrente - Ricezione	-

 SX1308P868GW Semtech 868MHZ PICOCELL GATEWAY V1.0 DEV	 SX1502I087TRT Semtech Corporation IC GPIO EXPANDER I2C 8CH 20QFN	 SX14.31818 30P-B TXC TXC SMD	 SX1501I087TRT Semtech Corporation IC GPIO EXPANDER I2C 4CH 20QFN
 SX1502EVK Semtech KIT EVAL SX1501/02	 SX1501087TRT Semtech IC GPIO EXPANDER I2C QFN	 SX1441EVK Semtech Corporation KIT DEV FOR SX1441	 SX1308P915GW Semtech 915MHZ PICOCELL GATEWAY V1.0 DEV

Di Più

Contact us: **Info@YIC-Electronics.com**

AGGIUNGI: Unit A5-B5 No.509, 5 / F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, Hong Kong.

Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited