

specificazioni	
Numero di parte	S2S4000F
fabbricante	Sharp Microelectronics
Descrizione	OPTOISOLATOR 3.75KV TRIAC 4SMD
Categoria	isolatori > Optoisolatori - Triac, uscita SCR
Stato parte	13260 pcs Stock
Diametro albero (mm)	Yes
Tensione - Stato off	600V
Tensione - Isolamento	3750Vrms
Tensione - Forward (Vf) (Typ)	1.2V
Attiva ora	50µs (Max)
Contenitore dispositivo fornitore	4-SMD
DV / dt statico (Min)	100V/µs
Serie	-
imballaggio	Tube
Contenitore / involucro	4-SMD
Tipo di uscita	Triac
temperatura di esercizio	-30°C ~ 100°C
Numero di canali	1
Tipo montaggio	Surface Mount
Corrente - Stato On (It (RMS)) (max)	50mA
Corrente - Trigger LED (Ift) (Max)	10mA
Corrente - Mantenimento (Ih)	3.5mA
Corrente - DC Forward (If) (Max)	50mA
Approvazioni	CSA, UR

 S2S4A000F SHARP S2S4A000F SHARP	 S2S4AY0F SHARP S2S4AY0F SHARP	 S2S3RY Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S4 Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD
 S2S4A00F Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S3Y Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S4A00F Socle Technology Corporation OPTOISOLATOR 3.75KV TRIAC 4SMD	 S2S3RY0F Sharp Microelectronics OPTOISOLATOR 3.75KV TRIAC 4SMD

Di Più

Contact us: **Info@YIC-Electronics.com**
AGGIUNGI: Unit A5-B5 No.509, 5 / F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, Hong Kong.
Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited