



specificazioni	
Modello di prodotti	HCPL-0201
fabbricante	Avago Technologies (Broadcom Limited)
Descrizione	OPTOISO 3.75KV PUSH PULL 8SO
Categoria	isolatori > Optoisolatori - Uscita logica
Stato parte	12599 pcs Stock
Tensione di alimentazione -	4.5 V ~ 20 V
Tensione - Isolamento	3750Vrms
Tensione - Forward (Vf) (Typ)	1.5V
Contenitore dispositivo fornitore	8-SO Tall
Serie	-
Tempo di salita / scadenza (Typ)	30ns, 7ns
Ritardo di propagazione tpLH / tpHL (Max)	300ns, 300ns
imballaggio	Tube
Contenitore / involucro	8-SOIC (0.154", 3.90mm Width)
Tipo di uscita	Push-Pull, Totem Pole
temperatura di esercizio	-40°C ~ 85°C
Numero di canali	1
Tipo montaggio	Surface Mount
Ingressi - Lato 1 / Lato 2	1/0
Tipo di ingresso	DC
Data Rate	5MBd
Corrente - Uscita / Canale	25mA
Corrente - DC Forward (If) (Max)	10mA
Immunità transitoria in modalità comune (Min)	1kV/μs

 HCPL-0201-000E Broadcom Limited OPTOISO 3.75KV PUSH PULL 8SO	 HCPL-0201#560 Broadcom Limited OPTOISO 3.75KV PUSH PULL 8SO	 HCPL--0639 FSC FSC SOP-8	 HCPL-0201#060 Broadcom Limited OPTOISO 3.75KV PUSH PULL 8SO
 HCPL 316J AVAGO	 HCPL-0201-060E Broadcom Limited OPTOISO 3.75KV PUSH PULL 8SO	 HCPL-0201#500 Broadcom Limited OPTOISO 3.75KV PUSH PULL 8SO	 HCPL 073L FAIRCHILD FAIRCHILD 2009+RoHS

Di Più

Contact us: **Info@YIC-Electronics.com**

AGGIUNGI: Unit A5-B5 No.509, 5 / F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, Hong Kong.

Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited