

specificazioni	
Numero di parte	SD7030-5R0-R
fabbricante	Bussmann (Eaton)
Descrizione	FIXED IND 4.9UH 3.2A 31 MOHM SMD
Categoria	Induttori, Bobine, Choke > Induttori fissi
Stato parte	27000 pcs Stock
Digitare	Wirewound
Tolleranza	±30%
Contenitore dispositivo fornitore	-
Dimensioni / Dimension	0.276" L x 0.276" W (7.00mm x 7.00mm)
Schermatura	Shielded
Serie	SD7030
Giudizi	-
Q alla frequenza	-
imballaggio	Original-Reel®
Contenitore / involucro	Nonstandard
temperatura di esercizio	-40°C ~ 125°C
Tipo montaggio	Surface Mount
Materiale - Nucleo	Ferrite
Induttanza	4.9µH
Altezza - In sede (max)	0.118" (3.00mm)
Frequenza - Prova	100kHz
Frequenza - Autorisonante	-
Resistenza cc (DCR)	31 mOhm Max
Valutazione attuale	3.2A
Corrente - saturazione	2.4A

 SD7030-820-R Eaton FIXED IND 81.4UH 820MA 390 MOHM	 SD7030-6R0-R Eaton FIXED IND 5.8UH 2.8A 35 MOHM SMD	 SD7030-680-R Eaton FIXED IND 66.6UH 850MA 304 MOHM	 SD7030-3R9-R Eaton FIXED IND 4.1UH 3.4A 27 MOHM SMD
 SD7030-440-R Eaton FIXED IND 43.4UH 1.1A 238 MOHM	 SD7030-681-R Eaton FIXED IND 677.2UH 280MA 3.847OHM	 SD7030-561-R Eaton FIXED IND 561UH 290MA 3.428 OHM	 SD7030-560-R Eaton FIXED IND 54.4UH 990MA 277 MOHM

Di Più

Contact us: **Info@YIC-Electronics.com**

AGGIUNGI: Unit A5-B5 No.509, 5 / F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, Hong Kong.

Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited