

specificazioni	
Modello di prodotti	PC365NJ0000F
fabbricante	Sharp Microelectronics
Descrizione	OPTOISO 3.75KV DARL 4-MINI-FLAT
Categoria	isolatori > Optoisolatori - Transistor, uscita fotovoltaica
Stato parte	1953 pcs Stock
Tensione - uscita (max)	35V
Tensione - Isolamento	3750Vrms
Tensione - Forward (Vf) (Typ)	1.2V
Vce saturazione (max)	1V
Accensione / spegnimento (Typ)	-
Contenitore dispositivo fornitore	4-Mini-Flat
Serie	-
Tempo di salita / scadenza (Typ)	60µs, 53µs
imballaggio	Tape & Reel (TR)
Contenitore / involucro	4-SMD, Gull Wing
Tipo di uscita	Darlington
temperatura di esercizio	-30°C ~ 100°C
Numero di canali	1
Tipo montaggio	Surface Mount
Tipo di ingresso	DC
Rapporto trasferimento corrente (min)	600% @ 500µA
Rapporto trasferimento corrente (max)	-
Corrente - Uscita / Canale	80mA
Corrente - DC Forward (If) (Max)	10mA

 PC365 SHARP PC365 SHARP	 PC367 SHARP PC367 SHARP	 PC364NT SHARP PC364NT SHARP	 PC367A SHARP PC367A SHARP
 PC364NJ0000F Socle Technology Corporation OPTOISO 3.75KV TRANS 4-MINI-FLAT	 PC365N Sharp Microelectronics OPTOISO 3.75KV DARL 4-MINI-FLAT	 PC364NTJ000F Sharp Microelectronics OPTOISO 3.75KV TRANS 4-MINI-FLAT	 PC365NTJ000F SHARP PC365NTJ000F SHARP

Di Più

Contact us: **Info@YIC-Electronics.com**
AGGIUNGI: Unit A5-B5 No.509, 5 / F Sing Win Factory Building, 15-17 Shing yip St, Kwun Tong, Kowloon, Hong Kong.
Copyright © 2023 YIC-Electronics.com - YIC International Co., Limited